

FEW/PT-8/HMVAC-VINTAGE



CALIBRATA

FEW/PT-8/HMVAC - VINTAGE

SPECIFICATION	QUANTITY
NO. OF CYLINDER	Eight
MAIN FABRICATED FRAME	6 mm M.S. Sheet, 26 " wide
NATURE OF DRIVE	A.C. Inverter Drive
MAIN ELECTRIC DRIVE	7.5 H.P. , 440 volts
FUEL SUPPLY MOTOR	1 H.P. 440 volts
DISPLAY	Touch HMI Through PLC
R.P.M. RANGE	0-4000 R.P.M.
PRESSURE GAUGES	0-7, 0-2.5, 0-21, 0-42 Bar(4" Dia)
OIL TANK	50 Liters (SS 304)
R.P.M. CONTROL	By Speed Booster & HMI
SWIVELING INJECTOR CONTROL	Height Adjustment By Jack, 320 mm Long Glass Tubes
FLYWHEEL	360 mm (Hard Crommed)
MOUNTING RAIL	M.S. Fabricated Heavy Duty
TRANSMISSION	By Virtue of V-belts from Main Motor to Housing
SOLENOID OPERATION	Dual
F.I.P. MOUNTING ACESSORIES	For Inline & Rotary (Heavy Duty)
INJECTORS	On Extra Cost As per Choice
FLEXIBLE COUPLING	95 mm