

# FEW/PT-8/TVAC-PRECISKO



# CALIBRATA

## FEW/PT-8/TVAC-PRECISKO

SPECIFICATION	QUANTITY
NO. OF CYLINDER	Eight
MAIN FABRICATED FRAME	6 mm section, 22 " wide
NATURE OF DRIVE	A.C. Inverter Drive
MAIN ELECTRIC DRIVE	5 H.P. , 440 volts or 220 volts
FUEL SUPPLY MOTOR	1 H.P. 440 volts or 220 volts
DISPLAY	Tachometer
R.P.M. RANGE	0-3000 R.P.M.
PRESSURE GAUGES	0-7, 0-2.5, 0-21, 0-42 Bar(2.5" Dia)
OIL TANK	40 Liters (M.S.)
R.P.M. CONTROL	By Speed Booster
SWIVELING INJECTOR CONTROL	Fixed 240 mm Long Glass Tubes
FLYWHEEL	300 mm (Hard Crommed)
MOUNTING RAIL	M.S. Fabricated
TRANSMISSION	By Virtue of V-belts from Main Motor to Housing
SOLENOID OPERATION	Single
F.I.P. MOUNTING ACESSORIES	For Inline & Rotary
INJECTORS	On Extra Cost As per Choice
FLEXIBLE COUPLING	95 mm