

# FEW/PT-8/TVAC-NAMMINY



# **CALIBRATA**

## **FEW/PT-8/TVAC-NAMMINY**

| <b>SPECIFICATION</b>              | <b>QUANTITY</b>                                 |
|-----------------------------------|---|
| <b>NO. OF CYLINDER</b>            | Eight   |
| <b>MAIN FABRICATED FRAME</b>      | 6 mm section, 22 " wide                         |
| <b>NATURE OF DRIVE</b>            | A.C. Inverter Drive                             |
| <b>MAIN ELECTRIC DRIVE</b>        | 5 H.P. , 440 volts or 220 volts                 |
| <b>FUEL SUPPLY MOTOR</b>          | 1 H.P. 440 volts or 220 volts                   |
| <b>DISPLAY</b>                    | Tachometer                                      |
| <b>R.P.M. RANGE</b>               | 0-3000 R.P.M.                                   |
| <b>PRESSURE GAUGES</b>            | 0-21, 0-42 Bar(4" Dia)                          |
| <b>OIL TANK</b>                   | 35 Liters (M.S.)                                |
| <b>R.P.M. CONTROL</b>             | By Speed Booster                                |
| <b>SWIVELING INJECTOR CONTROL</b> | Fixed 240 mm Long Glass Tubes                   |
| <b>FLYWHEEL</b>                   | 250 mm (Hard Crommed)                           |
| <b>MOUNTING RAIL</b>              | M.S. Fabricated                                 |
| <b>TRANSMISSION</b>               | By Virtue of V-belts from Main Motor to Housing |
| <b>SOLENOID OPERATION</b>         | Single  |
| <b>F.I.P. MOUNTING ACESSORIES</b> | For Inline & Rotary                             |
| <b>INJECTORS</b>                  | On Extra Cost As per Choice                     |
| <b>FLEXIBLE COUPLING</b>          | 95 mm   |