

FEW/PT-12/HMVAC-HERITAGE



CALIBRATA

FEW/PT-12/HMVAC-HERITAGE

SPECIFICATION	QUANTITY
NO. OF CYLINDER	Twelve
MAIN FABRICATED FRAME	8 mm M.S. Sheet, 26 " wide
NATURE OF DRIVE	A.C. Inverter Drive
MAIN ELECTRIC DRIVE	15H.P. 20H.P, 25H.P. , 440 volts
FUEL SUPPLY MOTOR	1.5 H.P. 440 volts
DISPLAY	Touch HMI Through PLC
R.P.M. RANGE	0-4000 R.P.M.
PRESSURE GAUGES	0-7, 0-2.5, 0-21, 0-42 Bar (4" Dia)
OIL TANK	50 Liters (SS 304)
R.P.M. CONTROL	By Speed Booster & HMI
SWIVELING INJECTOR CONTROL	Height Adjustment By Jack, 320 mm Long Glass Tubes
FLYWHEEL	360 mm (Hard Crommed)
MOUNTING RAIL	Solid Casted Heavy Duty
TRANSMISSION	By Direct Drive
SOLENOID OPERATION	Dual
F.I.P. MOUNTING ACESSORIES	For Inline & Rotary, P-Type Mounting
INJECTORS	On Extra Cost As per Choice
FLEXIBLE COUPLING	95 mm or 120 mm at extra cost
CHILLER WITH COMPRESSOR UNIT	For Maintaing the Temperature of Fuee
CIRCULATION PUMP SUPPLY	0.5 hp Motor with 3l/min Pump
CONDENSER	To Reduce the Temperature of Rail over Flow